

EATERS III SPEARMINT

ODOR CONTROLLER & WASTE DEGRADER

ARMCHEM

STABLE, LIQUID SUSPENSION OF SPORES AND VEGETATIVE MICROORGANISMS CAPABLE OF DIGESTING COMPLEX PROTEINS, STARCHES, FATS AND CELLULOSE AS WELL AS VEGETABLE GUMS.

BENEFITS-FEATURES:

- Digests complex organic waste compounds
- Culture grows in presence or absence of air
- Reduces suspended solids
- Eliminates malodors
- Pleasing spearmint scent

ADVANTAGES:

- USDA Authorized
- Non-pathogenic
- Non-polluting
- Non-toxic
- Non-acid
- Non-alkaline

WHERE TO USE:

Eaters III is highly effective on and around urinals and commodes where odors and germs are present. In addition this product is excellent when used on pet odors in carpets.

RECOMMENDED FOR:

- Toilet bowls / urinals
- Portable toilets
- Grease traps
- Drains / drain fields
- Sump pumps
- Sewage plants
- Pet odors



EATERS III SPEARMINT

ODOR CONTROLLER & WASTE DEGRADER

ARMCHEM

DIRECTIONS:

GENERAL DEODORIZATION: Spray product directly on malodor.

URIC ACID ODOR ELIMINATION: Remove solid matter. Spray directly on surfaces at location of odor. Works well on floor and wall around urinals and commodes.

GREASE TRAPS: For traps up to 500 gallon capacity, pour 4-5 oz. or as determined to be needed, on each day of use, in the sink or pipeline. This should be done when the lines are least used. Flush down with a cup of lukewarm water. For 500-1000 gallon traps, use 11-14 oz. For 1,000-2,000 gallon capacity traps, use 17-21 oz. in all situations use the same procedure. For convenience and best results, use our computerized pump system.

SEPTIC TANKS: Add 1 pint per 25 cu. ft. capacity, initially. Then use 8 oz. per week. Pour directly into toilet and flush. If a septic tank is clogged; add 1 gallon of product to tank through manhole.

RECREATIONAL VEHICLES AND BOATS: Add 2 oz. per gal, of water in hold tank, then use 1 oz. per gal as needed. For dump stations, use 1 oz. per 50 gals. of tank capacity. One pint per week for maintenance.

PORTA-TOILETS AND OUTHOUSES: Add 1 gal. and cover solids with water to aid digestion. Repeat treatment each time toilet is pumped.

DRAIN LINES & DOWN PIPES: Use products as listed below. Start on lowest floor and work 1 floor every day. Do not treat same floor twice. When top floor is reached, treat from top floor only.

PIPE SIZE	DOSAGE	FREQUENCY
2"	4 oz.	Twice a week
4"	8 oz.	Twice a week
6"	12 oz.	Twice a week
8"	16 oz.	Twice a week

SKU #

PACKAGING

HCS4884:

12 quarts per case

HCS4884-E:

5-gallon container

HCS4884-A:

55-gallon container



Chlorine, bleach, and heat resistant formula up to 200 ppm and 150 °F

WWW.ARMICHEM.COM
PHONE: 1-800-886-0423

ADDRESS: 3563 NW 53rd Ct,
Fort Lauderdale, FL 33309